

XXS mini 55BT

NEW



CHARACTERISTICS

• Designed for the maintenance and deep cleaning of large areas with a very important reduction of cleaning cost • **Very compact size and great maneuverability like walk behind models: suited for maintenance cleaning** • 28 kg of constant pressure on the brushes • Great working autonomy (3.5h) thanks to the possibility to use 2 batteries 12 V 105 Ah and to rear wheel-drive • Large load tank capacity, resulting in reduced numbers of stops and maximum use of battery for effective operation of the machine • Ergonomic steering wheel of new design with user friendly controls and digital display • Easy access to electrical components • Inspection cover for fast and easy cleaning and sanification of dirt water tank • Automatic device that stops brushes and detergent water outflow when the machine is stationary • Self-levelling brush plate • **Automatic detergent dosing system (optional)** • USB socket for mobile charging (optional) • Front working led light (optional) • Float filling system with aquastop (optional) • Hose filling system (optional)


TECHNICAL DATA

	XXS mini 55BT	XXS mini 55BT	XXS mini 55BT
code	37035-00001	37035-00027	37035-00003
power supply	24V	24V (Battery charger included)	24V (Battery and Battery charger included)
scrubbing/squeegee width	550/650mm	550/650mm	550/650mm
max working capacity	3000 m²/h	3000 m²/h	3000 m²/h
solution tank capacity	70 l/18.4 gal	70 l/18.4 gal	70 l/18.4 gal
recovery tank capacity	75 l/19.8 gal	75 l/19.8 gal	75 l/19.8 gal
traction	rear wheel-drive/300 W	rear wheel-drive/300 W	rear wheel-drive/300 W
RPM/pressure on the brushes	150/22 kg / 330.6/48.5 lbs	150/22 kg / 330.6/48.5 lbs	150/22 kg / 330.6/48.5 lbs
brush motor power	1 X 380 W	1 X 380 W	1 X 380 W
max gradient empty/full tank	13%/10%	13%/10%	13%/10%
depression/vacuum motor	1300 mmH ₂ O/400 W	1300 mmH ₂ O/400 W	1300 mmH ₂ O/400 W
dimension (cm)/weight	117x65x118/128 kg	117x65x118/131 kg	117x65x118/200 kg

PLUS



New control panel with electronics ready for FMS system



Large and easily inspectable tank



Chemical dispenser tank (optional)



Brush plate with automatic release and reattachment. Squeegee in protected position

STANDARD EQUIPMENT

• 10002-14574 PP brush Ø 533 mm - 21"	• 00005-02370 Front squeegee blade L704 mm Th. 3mm • 00005-02371 Oil-proof PU rear squeegee blade L736 mm Th. 3mm	• 00056-00108 On-board battery charger kit 24V 15A/20A (only for code models 37035-00027/37035-00003)	• 2 x 00055-00180 GEL Battery 12V 106A/C5-125A/C20 (only for code model 37035-00003)	
---	---	---	--	--

OPTIONAL

• 1x 00055-00173 LiFePO4 Battery 25,6V 60Ah 1536Wh	• 00056-00108 battery charger 24V 15A/20A 115VAC-230VAC GEL	• 00056-00109 battery charger 24V 30A 180-240VAC Li-PO4 AND. 80A	• 00005-02631 Polyurethane front blade L.704 TH.3 Sh.40 • 00005-02371 Polyurethane rear blade L.736 TH.3 Sh.40	• 10002-14572 Tynex brush Ø 533 mm-21" • 10002-14571 PP 03 brush Ø 533 mm-21" • 10002-14573 PES brush Ø 533 mm-21"
• 10002-14570 EWU drive disc Ø 505 mm-20"	(kit 5 pz) • 10001-09915 - Ø 533 mm-21"- beige • 10001-09920 - Ø 533 mm-21"- green • 10001-09925 - Ø 533 mm-21"- black	• 00014-01349 Filling tube L=1.7m	• 00008-01515 Filling kit with aquastop system	